

Pneufit Push-in šróbenia

Ø A = zodpovedajúci vonkajší priemer trubky. B = Závit (G pre valcový, R pre kuželový).
Nákresy s kompletnými rozmermi môžete nájsť na internetovej stránke www.maedler.sk

Otočné kolená s valcovým závitom

Produkt č.	Ø A mm	B
861 704 05	4	M5
861 704 18	4	G ¹ / ₈ A
861 704 28	4	G ¹ / ₄ A
861 706 05	6	M5
861 706 18	6	G ¹ / ₈ A
861 706 28	6	G ¹ / ₄ A
861 708 18	8	G ¹ / ₈ A
861 708 28	8	G ¹ / ₄ A
861 708 38	8	G ³ / ₈ A
861 710 28	10	G ¹ / ₄ A
861 710 38	10	G ³ / ₈ A
861 710 48	10	G ¹ / ₂ A
861 712 28	12	G ¹ / ₄ A
861 712 48	12	G ¹ / ₂ A



T-šróbenia

Produkt č.	Ø A mm
862 604 00	4
862 606 00	6
862 608 00	8
862 610 00	10
862 612 00	12



Otočné kolená 45° s O-kružkom

Produkt č.	Ø A mm	B
862 006 18	6	G ¹ / ₈ A
862 006 28	6	G ¹ / ₄ A
862 008 18	8	G ¹ / ₈ A
862 008 28	8	G ¹ / ₄ A



Kolená

Produkt č.	Ø A mm
862 104 00	4
862 106 00	6
862 108 00	8
862 110 00	10
862 112 00	12



Otočné kolená, priečkové

Produkt č.	Ø A mm
862 206 00	6
862 208 00	8
862 210 00	10



Kolená

Produkt č.	Ø A mm	Ø A1 mm
862 304 00	4	4
862 306 00	6	6
862 308 00	8	8



Pneufit PUSH-IN rýchlospojky

- Teleso vyrobené najmä z poniklovanej mosadze.
- Klasický dizajn..
- Prevádzkový tlak: max. 18 bar.
- Vacuum: max. -1 bar.